



WYMV.E326286 Telemetry Equipment for Use in Hazardous Locations

Page Bottom

Telemetry Equipment for Use in Hazardous Locations

[See General Information for Telemetry Equipment for Use in Hazardous Locations](#)

EXPRO METERS INC
50 BARNES PARK NORTH
WALLINGFORD, CT 06492 USA

E326286

Class I, Division 2, Groups A, B, C and D.

PassiveSONAR Flow Monitoring System consisting of:

Associated nonincendive field wiring apparatus, Transmitter Part No. TB8, followed by -xx, where x may be any alphanumeric combination, followed by -03 or -04 or alternatively Part No. TB8-xx-xx-xy, where x may be any alphanumeric combination, and y may be 0 or 1, followed by -02, for use in Class I, Division 2, Groups A, B, C and D Hazardous Locations Providing Nonincendive Field Circuits for use in Class I, Division 2, Groups A, B, C and D when connected per control drawing No. 20332-01.

Nonincendive field wiring apparatus, Sensor Head Model SH, followed by xxx-xx-xx, where x may be any alphanumeric combination or alternatively Model SH-xxx-xx-xx-xxx, where x may be any alphanumeric combination, followed by -02, for use in Class I, Division 2, Groups A, B, C and D when connected per control drawing No. 20332-01.

Associated nonincendive field wiring apparatus, Transmitter Part No. TB8, followed by -xx, where xx may be any alphanumeric combination, followed by -x5 or -x6, where x can be any alphanumeric, followed by -x, where x can be any alphanumeric, followed by x, where x can be any alphanumeric except 0 or 1, followed by -02 for use in Class I, Division 2, Groups A, B, C and D Hazardous Locations Providing Nonincendive Field Circuits for use in Class I, Division 2, Groups A, B, C and D when connected per control drawing No. 20944-01C.

Associated nonincendive field wiring apparatus, Transmitter Part No. TB8, followed by -xx, where xx may be any alphanumeric combination, followed by -x5 or -x6, where x can be any alphanumeric, followed by -x, where x can be any alphanumeric, followed by x, where x can be any alphanumeric except 0 or 1, followed by -05 for use in Class I, Division 2, Groups A, B, C and D Hazardous Locations when connected per control drawing No. 20945-01C.

Nonincendive field wiring apparatus, Sensor Head Model SH, followed by xxx-xx-xx-xxx, where x may be any alphanumeric, followed by -02, for use in Class I, Division 2, Groups A, B, C and D Hazardous Locations when connected per control drawing No 20944-01C.

Last Updated on 2008-11-25

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

